

Bermuda Gold 800 R 26/180, 2m RU

180 W



Article-No.

1012171-00

Reflector



VIT

JK-International GmbH Bereich Licht

Köhlershohner Straße

53578 Windhagen

Fon +49(0)2224-818-600

Fax +49(0)2224-818-615

E-Mail: info@jk-licht.de

Internet: www.jk-licht.de

Dimensions


Lamp Length	Nominal	2000 mm
	Face to Face (Base max.)	2000 mm
	Adapter to Adapt. (max.)	2008 mm
Diameter		38 mm
Base		G13 bi-pin gold

Electrical Data (nominal values)

Lamp Wattage	180 W
Lamp Current	1,7 A
Lamp Voltage	130 V
Compensation	18 µF
Ballast	180 W

Physical Data

(typical data)	
UVA Radiant Flux	50,0 W
UVB/UVA-Ratio (UVB: 280-315 nm)	2,8 %
UVB/UVA-Ratio (UVB: 280-320nm)	%
Recommended life time	800 h
Effective UV Power	
Ø < 320 nm	89.11 mW
Ø > 320 nm	20.94 mW
Ø Total nm	110.05 mW



Recommended exposure times at a typical UVA irradiance of 300 W/m².

Skin Type 2	3 min.
Skin Type 3	5 min.
Skin Type 4	6 min.

The recommended exposure times correspond approximately to the effective dose of:

250 J/m ²	for Skin Type 2
350 J/m ²	for Skin Type 3
450 J/m ²	for Skin Type 4

The effective dose is derived from the ultraviolet action curve in accordance with EN 60335-2-27.

(Technical modifications reserved)

Zurück

Drucken

